
datetime_truncate Documentation

Release 1.0.1

Björn Andersson / Media Pop

April 28, 2016

1	<code>datetime_truncate</code> <code>datetime_truncate</code>	3
2	Indices and tables	5
	Python Module Index	7

This module truncates a datetime object to the level of precision that you specify, making everything higher than that zero (or one for day and month).

It is based on PostgreSQL's [DATE_TRUNC](#).

datetime_truncate datetime_truncate

`datetime_truncate.truncate(datetime, truncate_to='day')`

Truncates a datetime to have the values with higher precision than the one set as *truncate_to* as zero (or one for day and month).

Possible values for *truncate_to*:

- second
- minute
- hour
- day
- week (iso week i.e. to monday)
- month
- quarter
- half_year
- year

Examples:

```
>>> truncate(datetime(2012, 12, 12, 12), 'day')
datetime(2012, 12, 12)
>>> truncate(datetime(2012, 12, 14, 12, 15), 'quarter')
datetime(2012, 10, 1)
>>> truncate(datetime(2012, 3, 1), 'week')
datetime(2012, 2, 27)
```

Params datetime an initialized datetime object

Params truncate_to The highest precision to keep its original data.

Returns datetime with *truncated_to* as the highest level of precision

Return type datetime datetime object

`datetime_truncate.truncate_second(datetime)`

Sugar for `truncate(datetime, 'second')`

`datetime_truncate.truncate_minute(datetime)`

Sugar for `truncate(datetime, 'minute')`

`datetime_truncate.truncate_hour(datetime)`

Sugar for `truncate(datetime, 'hour')`

`datetime_truncate.truncate_day(datetime)`

Sugar for `truncate(datetime, 'day')`

`datetime_truncate.truncate_week(datetime)`

Truncates a date to the first day of an ISO 8601 week, i.e. monday.

Params `datetime` an initialized datetime object

Returns `datetime` with the original day set to monday

Return type `datetime` datetime object

`datetime_truncate.truncate_month(datetime)`

Sugar for `truncate(datetime, 'month')`

`datetime_truncate.truncate_quarter(datetime)`

Truncates the datetime to the first day of the quarter for this date.

Params `datetime` an initialized datetime object

Returns `datetime` with the month set to the first month of this quarter

Return type `datetime` datetime object

`datetime_truncate.truncate_half_year(datetime)`

Truncates the datetime to the first day of the half year for this date.

Params `datetime` an initialized datetime object

Returns `datetime` with the month set to the first month of this half year

Return type `datetime` datetime object

`datetime_truncate.truncate_year(datetime)`

Sugar for `truncate(datetime, 'year')`

Indices and tables

- `genindex`
- `search`

d

`datetime_truncate`, 3

D

`datetime_truncate` (module), 3

T

`truncate()` (in module `datetime_truncate`), 3

`truncate_day()` (in module `datetime_truncate`), 4

`truncate_half_year()` (in module `datetime_truncate`), 4

`truncate_hour()` (in module `datetime_truncate`), 3

`truncate_minute()` (in module `datetime_truncate`), 3

`truncate_month()` (in module `datetime_truncate`), 4

`truncate_quarter()` (in module `datetime_truncate`), 4

`truncate_second()` (in module `datetime_truncate`), 3

`truncate_week()` (in module `datetime_truncate`), 4

`truncate_year()` (in module `datetime_truncate`), 4